

P8H61-M PLUS V2

Note: The specifications are subject to change without notice.

CPU	LGA1155 socket for Intel® Second Generation Core™ i7 / Core™ i5 / Core™ i3 processors Supports 32nm CPU Supports Enhanced Intel® SpeedStep Technology (EIST) * Refer to www.asus.com for Intel® CPU support list.
Chipset	Intel® H61 Express Chipset
Memory	2 x DIMM, max. 16GB*, DDR3 1333 / 1066 MHz, non-ECC, un-buffered memory Dual channel memory architecture Supports Intel® Extreme Memory Profile (XMP) * The maximum 16GB memory capacity can be supported with 8GB or above DIMMs. ASUS will update the memory QVL once the DIMMs are available in the market. ** Refer to www.asus.com for the latest Memory QVL (Qualified Vendors List). *** When you install a total memory of 4GB capacity or more, Windows® 32-bit operating system may only recognize less than 3GB. We recommend a maximum of 3GB system memory if you are using a Windows® 32-bit operating system.
Expansion Slots	1 x PCI Express 2.0 x16 slot 2 x PCI Express 2.0 x1 slot 1 x PCI slot
Storage	Intel® H61 Express Chipset - 4 x Serial ATA 3.0 Gb/s connectors
LAN	Realtek® 8111E Gigabit LAN controller
Audio	Realtek® ALC887 8-channel* High Definition Audio CODEC * Use a chassis with HD audio module in the front panel to support an 8-channel audio output.
USB	Intel® H61 Express Chipset: - 8 x USB 2.0/1.1 ports (4 ports at the mid-board, 4 ports at the back panel)
ASUS Unique Features	ASUS Anti-Surge Protection ASUS EFI BIOS ASUS GPU Boost ASUS ESD Guard ASUS CrashFree BIOS 3 ASUS EZ Flash 2 ASUS MyLogo 2™ 100% All High-quality Conductive Polymer Capacitors
Back Panel I/O Ports	1 x PS/2 keyboard port 1 x PS/2 mouse port 1 x DVI-D port 1 x D-Sub port 1 x LAN (RJ45) ports 4 x USB 2.0/1.1 ports 3 x Audio Jacks
Internal I/O Connectors	2 x USB 2.0/1.1 connectors support additional 4 USB 2.0/1.1 ports 4 x SATA 3.0 Gb/s connectors 1 x CPU fan connector 1 x Chassis fan connector 1 x Front panel audio connector 1 x S/PDIF Out connector 1 x COM port connector 1 x System panel connector 1 x 24-pin ATX Power connector 1 x 4-pin ATX 12V Power connector
BIOS	32 Mb Flash ROM, EFI BIOS, PnP, DMI v2.0, WfM 2.0, ACPI v2.0a, SM BIOS v2.6, Multi-language BIOS
Accessories	2 x Serial ATA 3.0Gb/s cables 1 x IO Shield 1 x SDVD 1 x User's manual
Support DVD	Drivers ASUS Utilities ASUS Update Anti-virus software (OEM version)
Form Factor	MicroATX form factor: 9.6 in x 8 in (24.4 cm x 20.3 cm)